

## **LED FIXTURE SPECIFICATION** MODEL# WAF



FINAL MODEL#	
PROJECT	
TYPE	
NOTES	

## **STANDARD FEATURES:** QUALITY LED WRAP

Fixture thermally tested to ensure longevity Maximum light distribution throughout lens Over current/voltage short circuit protection UL and/or CSA Compliant Listed

A quality, durable LED wrap around fixture For use in multi purpose applications, fabricated with reliable, thermally tested light engines

Constant Current Design

**FIXTURE LED ENGINE** LG/NICHIA/SAMSUNG, LED CHIPS BASE 20 Ga Steel Construction **FINISH** White **LUMENS PER WATT** AVG 92-107 @Module Efficacy **LENS** Clear Prismatic Arylic **LOCATION** Indoor Damp **DRIVER 120/277 VOLTS 50/60Hz** COMPLIANT COMPLIANT **POWER FACTOR** High **LIFE HOURS** 50,000 **DIMMABLE 0-10V WARRANTY** Limited 5 Years MADE IN AMERICA **TESTED** LM79 LM80

	48-1/2*	-
2-1/2" 000		

LEDILGUT			EXAMPLE	'		SIZE OPTIONS
SOURCE OPTIONS	WATTAGE: 32	KELVIN: 4	KELVIN: 4000k		L25 L48	
ORDERING INFORMATION:	WATTAGE:	KELVIN:	_	SIZE:	L46	vvo-/: п2 /-
CVCTEM WATTACE	2700K	3000K	3500K	4000K	5000K	LEGACY

SYSTEM WATTAGE	2700K WARM WHITE	3000K SOFT WHITE	3500K NEUTRAL	4000K COOL WHITE	5000K DAYLIGHT	LEGACY EQUIVALENT
25						
32			2882	2926	3017	(2-3) T817
(483/4)						
20			2169	2170	2235	(1-2) T832
32			3184	3233	3583	(2) T832 / (1) T554HO
48			4556	4625	4923	(3-4) T832 / (2) T554HO

## **SPECIAL OPTIONS** (please specify if applicable)

DRIVER: DVD	FINISH: FCU	LO	ACCESSO- FUS		TECHNOL- CT	
DRIVER:	FINISH:	LENS:	ACCESSORIES:		TECHNOLOGY:	
DRIVER	FINISH	LENS	ACCESSORIES		TECHNOLOGY	
□ <b>DV</b> 120/277 (Non Dimmable)	□ <b>FCU</b> Custom	□ LCU Custom	□ CHK Cable Hanging Kit □ PK2 Canopy/Pendant Kit/2 Rods □ WG Wire Guard	☐ BLD☐ CT☐ EMG☐ EMG☐ OSC☐ OSC	LED Color Tuning  Emergency (Any Lumens Package)  R Emergency Remote Occupancy Sensor On/Off	

## **ASL LIGHTING**