



LED FIXTURE SPECIFICATION

MODEL # **HBN**



FINAL MODEL #	
PROJECT	
TYPE	
NOTES	

STANDARD FEATURES: ROUND LED HIGHBAY

Fixture thermally tested to ensure longevity
Maximum light distribution throughout lens
Over current/voltage short circuit protection
UL and/or CSA Compliant Listed
Constant Current Design

Low profile, featuring annular polished optic for 700 narrow Beam spread. Standard hookup, Radial aluminum heat sink fins to insure durability and performance

FIXTURE	LED ENGINE
BASE Aluminum Construction	LG/NICHIA/SAMSUNG, LED CHIPS
FINISH Aluminum	LUMENS PER WATT AVG 96-117 @Module Efficacy
LENS Polycarbonate	KELVIN CRI 83
LOCATION Indoor Damp	DRIVER 120/277 VOLTS 50/60Hz
COMPLIANT RoHS	POWER FACTOR High
LIFE HOURS 50,000	DIMMABLE 0-10V
WARRANTY Limited 5 Years	TESTED LM79 LM80



LED LIGHT SOURCE OPTIONS

ORDERING INFORMATION:

EXAMPLE

WATTAGE: 150 KELVIN: 5000k SIZE: 2x4

WATTAGE: KELVIN: SIZE:

SIZE OPTIONS
D11 ^{3/4} H10

SYSTEM WATTAGE	2700K WARM WHITE	3000K SOFT WHITE	3500K NEUTRAL	4000K COOL WHITE	5000K DAYLIGHT	LEGACY EQUIVALENT
100					11,660	MH250
150					14,969	MH400

SPECIAL OPTIONS (please specify if applicable)

EXAMPLE

DRIVER: DVD FINISH: FCU LCU ACCESSO- FUS TECHNOLOGY: CT

DRIVER: FINISH: LENS: ACCESSORIES: TECHNOLOGY:

DRIVER	FINISH	LENS	ACCESSORIES	TECHNOLOGY
<input type="checkbox"/> DV 120/277 (Non Dimmable)	<input type="checkbox"/> FCU Custom	<input type="checkbox"/> LCU Custom	<input type="checkbox"/> CPK Canopy Pendant Kit <input type="checkbox"/> WG Wire Guard	<input type="checkbox"/> BLD Bi-Level Dimming <input type="checkbox"/> CT LED Color Tuning <input type="checkbox"/> EMG Emergency (Any Lumens Package) <input type="checkbox"/> EMGR Emergency Remote <input type="checkbox"/> OS Occupancy Sensor On/Off <input type="checkbox"/> OSCD Occupancy Sensor Step Dimming

