



# LED FIXTURE SPECIFICATION

## MODEL # RTELP



FINAL MODEL #	
PROJECT	
TYPE	
NOTES	

### STANDARD FEATURES: EDGE LIT LED LIGHT PANEL

Fixture thermally tested to ensure longevity  
 Maximum light distribution throughout lens  
 Over current/voltage short circuit protection  
 UL and/or CSA Compliant Listed  
 Constant Current Design

Flat LED panel provides flush fit into most drop ceilings, while providing even, consistent shadowless light and high performance

FIXTURE	LED ENGINE
<b>BASE</b> Extruded Aluminum <b>FINISH</b> White <b>LENS</b> Translucent White <b>LOCATION</b> Indoor Damp <b>COMPLIANT</b> RoHS <b>LIFE HOURS</b> 75,000 <b>WARRANTY</b> Limited 5 Years	<b>LG/NICHIA/SAMSUNG, LED CHIPS</b> <b>LUMENS PER WATT</b> AVG 90-100 @Module Efficacy <b>KELVIN</b> 35K 41K 50K <b>CRI</b> 80 <b>DRIVER</b> 120/277 VOLTS 50/60Hz <b>POWER FACTOR</b> High <b>DIMMABLE</b> 0-10V <b>TESTED</b> LM79 LM80



### LED LIGHT SOURCE OPTIONS

ORDERING INFORMATION:

EXAMPLE

WATTAGE: 36	KELVIN: 4100k	SIZE: 1x4
WATTAGE:	KELVIN:	SIZE:

SIZE OPTIONS		
L23 <sup>4/5</sup>	W23 <sup>4/5</sup>	H2
L47 <sup>4/5</sup>	W11 <sup>4/5</sup>	H2
L47 <sup>4/5</sup>	W23 <sup>4/5</sup>	H2

SYSTEM WATTAGE	2700K WARM WHITE	3000K SOFT WHITE	3500K NEUTRAL	4000K COOL WHITE	5000K DAYLIGHT	LEGACY EQUIVALENT
(1x4 / 2x2)						
36			3300	3375	3450	(3-4) T817
(2 x 4)						
45			4100	4300	4500	(2-3) T832

### SPECIAL OPTIONS (please specify if applicable)

EXAMPLE

DRIVER: DVD	FINISH: FCU	LENS: LCU	ACCESSO- FUS	TECHNOL- CT
DRIVER:	FINISH:	LENS:	ACCESSORIES:	TECHNOLOGY:

DRIVER	FINISH	LENS	ACCESSORIES	TECHNOLOGY
<input type="checkbox"/> DV 120/277 (Non Dimmable)	<input type="checkbox"/> FCU Custom	<input type="checkbox"/> LCU Custom		<input type="checkbox"/> BLD Bi-Level Dimming <input type="checkbox"/> CT LED Color Tuning <input type="checkbox"/> EMG Emergency (Any Lumens Package) <input type="checkbox"/> EMGR Emergency Remote <input type="checkbox"/> OS Occupancy Sensor On/Off <input type="checkbox"/> OSCD Occupancy Sensor Step Dimming

