



LED FIXTURE SPECIFICATION

MODEL # WPLOS



FINAL MODEL #	
PROJECT	
TYPE	
NOTES	

STANDARD FEATURES: LED CHANNEL/OCCUPANCY SENSOR

Fixture thermally tested to ensure longevity
 Maximum light distribution throughout lens
 Over current/voltage short circuit protection
 UL and/or CSA Compliant Listed
 Constant Current Design

Architectural LED luminate
 Contoured style. Low profile
 Low glare optics, Fabricated
 of non-corrosive quality materials
 Mounts to surface or suspended



FIXTURE	LED ENGINE
BASE Extruded Aluminum FINISH White LENS Translucent White LOCATION Indoor Damp COMPLIANT RoHS LIFE HOURS 50,000 WARRANTY Limited 5 Years	LG/NICHIA/SAMSUNG, LED CHIPS LUMENS PER WATT AVG 90-98 @Module Efficacy KELVIN 27K 30K 35K 41K CRI 83 DRIVER 120/277 VOLTS 50/60HZ POWER FACTOR High DIMMABLE 0-10V TESTED LM80

LED LIGHT SOURCE OPTIONS

ORDERING INFORMATION:

EXAMPLE

WATTAGE: 21 KELVIN: 3500K SIZE: 51

WATTAGE: KELVIN: SIZE:

SIZE OPTIONS
L51 W4 H2 ^{1/2}

SYSTEM WATTAGE	2700K WARM WHITE	3000K SOFT WHITE	3500K NEUTRAL	4000K COOL WHITE	5000K DAYLIGHT	LEGACY EQUIVALENT
21			32000	2027		(2) T817 / (1) T832
43			3500	3948		(2) T832

SPECIAL OPTIONS (please specify if applicable)

EXAMPLE

DRIVER: DVD FINISH: FCU LCU ACCESSO- FUS TECHNOLOGY: CT

DRIVER: FINISH: LENS: ACCESSORIES: TECHNOLOGY:

DRIVER	FINISH	LENS	ACCESSORIES	TECHNOLOGY
<input type="checkbox"/> DV 120/277 (Non Dimmable)	<input type="checkbox"/> FCU Custom	<input type="checkbox"/> LCU Custom	<input type="checkbox"/> CHK Cable Hanging Kit <input type="checkbox"/> ICK Interconnect Joiner Kit <input type="checkbox"/> PK2 Canopy/Pendant Kit/2 Rods <input type="checkbox"/> TBC T-Bar Twist-On Clip	<input type="checkbox"/> BLD Bi-Level Dimming <input type="checkbox"/> CT LED Color Tuning <input type="checkbox"/> EMG Emergency (Any Lumens Package) <input type="checkbox"/> EMGR Emergency Remote <input type="checkbox"/> OS Occupancy Sensor On/Off <input type="checkbox"/> OSCD Occupancy Sensor Step Dimming

