



LED FIXTURE SPECIFICATION

MODEL # WVTOS



FINAL MODEL #	
PROJECT	
TYPE	
NOTES	

STANDARD FEATURES: VAPORPROOF/OCCUPANCY SENSOR

Fixture thermally tested to ensure longevity
 Maximum light distribution throughout lens
 Over current/voltage short circuit protection
 UL and/or CSA Compliant Listed
 Constant Current Design

Economical LED vapor
 Tight, sealed fixture
 With omni directional
 Infrared dimmable sensor
 All non corrosive

FIXTURE	LED ENGINE
BASE Polycarbonate FINISH White LENS Translucent White LOCATION Indoor/Outdoor Wet	LG/NICHIA/SAMSUNG, LED CHIPS LUMENS PER WATT AVG 96-112 @Module Efficacy KELVIN 27K 30K 35K 40K 50K CRI 83 DRIVER 120/277 VOLTS 50/60Hz POWER FACTOR High DIMMABLE 0-10V TESTED LM79 and LM80
COMPLIANT	
LIFE HOURS 54,000 WARRANTY Limited 5 Years	



LED LIGHT SOURCE OPTIONS

ORDERING INFORMATION:

EXAMPLE

WATTAGE: 48 KELVIN: 5000k SIZE: 50

WATTAGE: KELVIN: SIZE:

SIZE OPTIONS		
L30 ^{1/4}	W6 ^{3/4}	H4 ^{3/4}
L54 ^{1/4}	W6 ^{3/4}	H4 ^{3/4}

SYSTEM WATTAGE	2700K WARM WHITE	3000K SOFT WHITE	3500K NEUTRAL	4000K COOL WHITE	5000K DAYLIGHT	LEGACY EQUIVALENT
(30 ^{1/4})				3082	3113	(3) T817 / (2) T524
32						
(54 ^{1/4})						
31				3506	3937	(3)T332 / (2) T554HO
48				4998	5043	(4) T832

SPECIAL OPTIONS (please specify if applicable)

EXAMPLE

DRIVER: DVD FINISH: FCU LCU ACCESSO- FUS TECHNOLOGY: CT

DRIVER: FINISH: LENS: ACCESSORIES: TECHNOLOGY:

DRIVER	FINISH	LENS	ACCESSORIES	TECHNOLOGY
<input type="checkbox"/> DV 120/277 (Non Dimmable)	<input type="checkbox"/> FCU Custom	<input type="checkbox"/> LCU Custom	<input type="checkbox"/> CHK Cable Hanging Kit <input type="checkbox"/> PK2 Canopy/Pendant Kit/2 Rods	<input type="checkbox"/> BLD Bi-Level Dimming <input type="checkbox"/> CT LED Color Tuning <input type="checkbox"/> EMG Emergency (Any Lumens Package) <input type="checkbox"/> EMGR Emergency Remote <input type="checkbox"/> OS Occupancy Sensor On/Off <input type="checkbox"/> OSCD Occupancy Sensor Step Dimming

